Engine Section Priper of lengine Section Sect	Passat Alltrack 2.0 TDI		110 kW (150 PS)
Effective displacement 0m3 1,968 Valves per cylinder I liquición / Charge Common Rail / Turbocharger Power output 110 (150) kW (PS) 3,500 - 4,000 at promone de la composition on the provincion of the provincio	Engine, electrics		
Valves per cylinder			4-cyl diesel engine TDI SCR BMT
Injection / Charge Common Rall / Turbocharger Power output Nm at pm 340 / 1,750 - 3,000 at pm Akt rorque Akt		cm ³	<i>,</i>
Nm at rm			
Max. torque Nm at tym 340 / 1,750 - 3,000 Alternator A 1440 Driving performance data 3 6,4 / 9.2 Acceleration 0 - 8100 km/h s 6,4 / 9.2 Acceleration 0 - 9100 km/h s 8 / 10.5 Top speed km/h 205 Fuel consumption Uses Dissel min. 51 CN Fuel page 1/100km 4.3 Combined cycle 1/100km 4.3 Combined cycle 1/100km 4.3 Coz emissions, combined g/km 130 - 129 Nox mg/km 4.38 Particulates mg/km 4.38 Efficiency label A Euro 6 Exterior dimensions Euro 6 Power transmission Easteror dimensions Six-speed manual gearbox 4MCTION four-wheel drive Exterior dimensions 4 4 Number of dors 4 4 Length with boving bracket (maximum length) mm 1,500 - 1,530 Written with dovin ritrors mm 2,002 - 1,202			
Alternator Å 140 Driving performance data 2 Acceleration 0 - 80/100 km/h \$ 6.4 / 9.2 Acceleration 80 - 120 km/h, 4th/sh gear \$ 8 / 10.5 Top speed km/h 205 Fuel consumption Dlesel min. 51 CN Fuel type Dlesel min. 51 CN Urban 1/100km 4.3 Combined cycle 1/100km 4.9 CO2 emissions, combined g/km 130-129 NOX mg/km 43.8 Particulates mg/km 43.8 Efficiency label A Euro 6 Power transmission Euro 6 Euro 6 Power transmission Tuend 6 Euro 6 Exterior dimensions Tuend 77 - 4,882 4 Number of doors Tuend 77 - 4,882 4 Length with towing bracket (maximum length) mm 1,832 - 1,832 4 Width with door mirrors mm 2,062 2 Wheelbase mm 1,582 / 1,585 4			
Driving performance data Acceleration 0 - 80/100 km/h \$ 6.4/9.2 Acceleration 0 - 80/100 km/h 4th/9.2 5 8/10.5 Acceleration 0 - 80/100 km/h 4th/9.2 5 8/10.5 Top speed Mrwh 205 205 Fuel consumption Power transman 1/100km 4.3 Urban 1/100km 4.3 4.9 Combined cycle 1/100km 4.3 4.9 CO2 emissions, combined g/km 130 - 129 135 135 140 135 140 135 140 135 140 135 140 135 140 <	· ·		· · · · · · · · · · · · · · · · · · ·
Acceleration 0 - 80/100 km/h 4 (4) 9.2 Acceleration Bo - 120 km/h, 4th/5th gear s 8 / 10.5 Top speed km/h 205 Fuel consumption Diesel min. 51 CN Fuel type Diesel min. 51 CN Urban 1/100km 4.3 Combined cycle 1/100km 4.9 CO2 emissions, combined g/km 130-129 NOX mg/km 43.8 Particulates mg/km 43.8 Efficiency label A Euro 6 Power transmission Euro 6 Euro 6 Power transmission Six-speed manual gearbox 4MOTION four-wheel drive Exterior dimensions 4 A Number of doors 4 4 A Exterior dimensions 4 4 A A Width mm 1,506 - 1,530 A A A A A A A A A A A A A A A A A A		A	140
Acceleration 80 - 120 km/h, 4th/5th gear			2.442
Top speed km/h 205 Fuel type Diesel min. 51 CN Livian 1/100km 5.9 Extra-urban 1/100km 4.9 CO2 emissions, combined g/km 130-129 NOx mg/km 43.8 Particulates mg/km 43.8 Efficiency label A Ebros Efficiency label Euro 6 Euro 6 Power transmission Starbox Six-speed manual gearbox 4MOTION four-wheel drive Exterior dimensions Number of doors Track, from manual gearbox 4MOTION four-wheel drive Exterior dimensions Track, from manual gearbox 4MOTION four-wheel drive Width mm 4,777-4,882 Width mm 1,832-1,832 Height mm 4,777-4,882 Width with door mirrors mm 2,062 Width with door mirrors mm 1,552-1,155 Approach angle / departure angle nm 1,552-1,155 Breakover angle <td></td> <td></td> <td></td>			
Fuel type	, ,		
Fuel type		Km/n	205
Urban	•		D: 1 : 51 ON
	* *	1/4001	
Combined cycle I/100km 4,9 CO2 emissions, combined g/km 130 - 129 NOX mg/km 43.8 Particulates mg/km 1.35 Efficiency label Euro 6 Power transmissions Euro 6 Earbox Six-speed manual gearbox 4MOTION four-wheel drive Exterior dimensions 4 Number of doors 4 Length mm 4,777 - 4,882 Width mm 1,532 - 1,832 Height mm 1,582 - 1,832 United by with towing bracket (maximum length) mm 1,565 - 1,530 Length with towing bracket (maximum length) mm 2,062 Wheelbase mm 2,789 Track, front / rear mm 1,582 / 1,565 Approach angle / departure angle " 13.4 / 12.3 Breakover angle " 13.4 / 12.3 Breakover angle " 10.5 Turning circle mm 11.4 Interior dimensions f 5			
CO2 emissions, combined g/km 130 - 129 NOX mg/km 43.8 Particulates mg/km 1.35 Efficiency label Euro 6 Exhaust emissions classification Euro 6 Power transmission Six-speed manual gearbox 4MOTION four-wheel drive Exterior dimensions 4 Number of doors 4 Length mm 4,777 - 4,882 Width mm 1,832 - 1,832 Height mm 1,832 - 1,832 Height with towing bracket (maximum length) mm 1,832 - 1,832 Height with door mirrors mm 2,062 Width with door mirrors mm 2,769 Track, front / rear mm 1,582 / 1,565 Approach angle / departure angle ° 13.4 / 12.3 Breakover angle ° 13.4 / 12.3 Breakover angle ° 13.5 / 12.56 Turning circle m 11.4 Interior dimensions 5 5 Number of seats 5 5			
NOx	1		
Particulates	·	•	
Efficiency label A Exhaust emissions classification Euro 6 Power transmission Six-speed manual gearbox 4MOTION four-wheel drive Exterior dimensions 4 Number of doors 4 Length mm 4,777 - 4,882 Width mm 1,832 - 1,832 Height mm 1,506 - 1,530 Length with towing bracket (maximum length) mm 4,882 Width with door mirrors mm 2,062 Wheelbase mm 2,789 Track, front / rear mm 1,582 / 1,565 Approach angle / departure angle ° 10,5 Breakover angle ° 10,5 Turning circle m 11,4 Interior dimensions 5 Number of seats 5 Head area: 1st seat row / 2nd seat row / 3rd seat row mm 952 / 980 row / 3rd seat row mm 1,053 / 960 Head area: 1st seat row / 2nd seat row / 3rd seat row mm 1,053 / 960 Interior dimensions mm 1,053 / 9			
Exhaust emissions classification Euro 6 Fower transmission Gearbox Six-speed manual gearbox 4MOTION four-wheel drive Exterior dimensions 4 Number of doors 4 Length mm 4,777 - 4,882 Width mm 1,506 - 1,530 Length with towing bracket (maximum length) mm 2,062 Width with door mirrors mm 2,062 Wheelbase mm 2,789 Track, front / rear mm 1,582 / 1,565 Approach angle / departure angle ° 13.4 / 12.3 Breakover angle ° 10.5 Turning circle m 11.4 Interior dimensions 5 Number of seats 5 Head area: 1st seat row / 2nd seat row / 3rd seat row mm 970 / 980 Head area: 1st seat row / 2nd seat row / 3rd seat row mm 952 / 980 row / 3rd seat row mm 1,053 / 960 Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,053 / 960 Interior width: 1st seat row / 2nd seat row / 3rd seat row <th< td=""><td></td><td>mg/km</td><td></td></th<>		mg/km	
Power transmission Gearbox Six-speed manual gearbox 4MOTION four-wheel drive	· · · · · · · · · · · · · · · · · · ·		
Gearbox Six-speed manual gearbox 4MOTION four-wheel drive Exterior dimensions 4 Length mm 4,777 - 4,882 Width mm 1,832 - 1,832 Height mm 1,506 - 1,530 Length with towing bracket (maximum length) mm 1,506 - 1,530 Length with towing bracket (maximum length) mm 4,882 Width with door mirrors mm 2,062 Wheelbase mm 2,789 Track, front / rear mm 1,582 / 1,565 Approach angle / departure angle ° 13.4 / 12.3 Breakover angle ° 10.5 Interior dimensions 5 Head area: 1st seat row / 2nd seat row / 3rd seat row mm 970 / 980 Head area (glass sunroof): 1st seat row / 2nd seat row / mm 952 / 980 row / 3rd seat row mm 1,053 / 960 Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,053 / 960 Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,053 / 960 Usuagage compartment mm 1,000 <td></td> <td></td> <td>Lui 0 0</td>			Lui 0 0
Number of doors		Six	x-speed manual gearbox 4MOTION four-wheel drive
Length	Exterior dimensions		
Width mm 1,832 - 1,832 Height mm 1,506 - 1,530 Length with towing bracket (maximum length) mm 4,882 Width with door mirrors mm 2,062 Wheelbase mm 2,789 Track, front / rear mm 1,582 / 1,565 Approach angle / departure angle ° 13,4 / 12.3 Breakover angle ° 10.5 Turning circle m 11.4 Interior dimensions Number of seats 5 Head area: 1st seat row / 2nd seat row / 3rd seat row mm 970 / 980 Head area: 1st seat row / 2nd seat row / 2nd seat row mm 952 / 980 row / 3rd seat row mm 1,053 / 960 Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,466 / 1,511 / row Luggage compartment Legroom: 1st seat row / 2nd seat row / 3rd seat row mm 1,172 / 2,018 Width between wheel housings mm 1,000 Load height up to headlining mm 1,000 Volume by VDA measur	Number of doors		4
Height	Length	mm	4,777 - 4,882
Length with towing bracket (maximum length) mm 4,882 Width with door mirrors mm 2,062 Wheelbase mm 2,789 Track, front / rear mm 1,582 / 1,565 Approach angle / departure angle ° 13.4 / 12.3 Breakover angle ° 10.5 Turning circle m 11.4 Interior dimensions Number of seats 5 Head area: 1st seat row / 2nd seat row / 3rd seat row mm 970 / 980 Head area: (glass sunroof): 1st seat row / 2nd seat row mm 952 / 980 row / 3rd seat row mm 1,053 / 960 Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,466 / 1,511 / row Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,466 / 1,511 / row Luggage compartment Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,053 / 960 Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,172 / 2,018 mm Width between wheel housings mm 1,053 / 960	Width	mm	
Width with door mirrors mm 2,062 Wheelbase mm 2,789 Track, front / rear mm 1,582 / 1,565 Approach angle / departure angle ° 13.4 / 12.3 Breakover angle ° 10.5 Turning circle m 11.4 Interior dimensions Number of seats 5 Head area: 1st seat row / 2nd seat row / 3rd seat row mm 970 / 980 Head area: 1st seat row / 2nd seat row / 2nd seat row mm 952 / 980 row / 3rd seat row mm 1,053 / 960 Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,466 / 1,511 / row 1st seat row / 2nd seat row / 3rd seat row mm 1,466 / 1,511 / row 1st seat row / 2nd seat row / 3rd seat row mm 1,466 / 1,511 / row 1st seat row / 2nd seat row / 3rd seat row mm 1,466 / 1,511 / row 2nd seat row / 2nd seat row / 3rd seat row mm 1,466 / 1,511 / Legroom: 1st seat row / 2nd seat row / 3rd seat row mm 1,172 / 2,018 Width	_ ~	mm	
Wheelbase mm 2,789 Track, front / rear mm 1,582 / 1,565 Approach angle / departure angle ° 13.4 / 12.3 Breakover angle ° 10.5 Turning circle m 11.4 Interior dimensions Number of seats 5 Head area: 1st seat row / 2nd seat row / 3rd seat row mm 970 / 980 Head area (glass sunroof): 1st seat row / 2nd seat row / 2nd seat row mm 952 / 980 row / 3rd seat row mm 1,053 / 960 Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,466 / 1,511 / row mm 1,466 / 1,511 / row mm 1,466 / 1,511 / row mm 1,053 / 960 Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,466 / 1,511 / row mm 1,053 / 960 Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,172 / 2,018 Width between wheel housings mm 1,000 Legroum: 4 big difference 639 - 1,769	, , , , , , , , , , , , , , , , , , , ,	mm	·
Track, front / rear mm 1,582 / 1,565 Approach angle / departure angle ° 13.4 / 12.3 Breakover angle ° 10.5 Turning circle m 11.4 Interior dimensions Number of seats 5 Head area: 1st seat row / 2nd seat row / 3rd seat row mm 970 / 980 Head area: (st seat row / 2nd seat row / 2nd seat row / 3rd seat row mm 952 / 980 row / 3rd seat row mm 1,053 / 960 Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,466 / 1,511 / row Luggage compartment Length, rear seat raised/folded down mm 1,172 / 2,018 Width between wheel housings mm 1,000 Load height up to headlining mm 831 Volume by VDA measurement I 639 - 1,769 Luggage compartment opening: width/height mm 1,014 / 333 Weights Kerb weight (EU, incl. 75 kg driver) kg 1,670 - 1,851 Permitted gross weight kg 2,260 Paylo			
Approach angle / departure angle ° 13.4 / 12.3 Breakover angle ° 10.5 Turning circle m 11.4 Interior dimensions 5 Head area: 1st seat row / 2nd seat row / 3rd seat row mm 970 / 980 Head area: 1st seat row / 2nd seat row / 2nd seat row mm 952 / 980 Head area (glass sunroof): 1st seat row / 2nd seat row mm 1,053 / 960 Interior width: 1st seat row / 2nd seat row 3rd seat row mm 1,466 / 1,511 / row			·
Approach angle / departure angle 10.5 Turning circle m 11.4 Interior dimensions 5 Head area: 1st seat row / 2nd seat row / 3rd seat row mm 970 / 980 Head area (glass sunroof): 1st seat row / 2nd seat row mm 952 / 980 row / 3rd seat row 2nd seat row / 3rd seat row mm 1,053 / 960 Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,466 / 1,511 / row Luggage compartment Length, rear seat raised/folded down mm 1,172 / 2,018 Width between wheel housings mm 1,000 Load height up to headlining mm 831 Volume by VDA measurement I 639 - 1,769 Luggage compartment opening: width/height mm 1,014 / 333 Weights Kerb weight (EU, incl. 75 kg driver) kg 1,670 - 1,851 Permitted gross weight kg 2,260 Payload from / to kg 484 - 665 Permitted axle load, front/rear kg 1,100 / 1,210 Allowable trailer weight, unbraked kg 2,200 / 2,200 Allowable trailer weight, unbraked kg 750 Permitted drawbar weight/roof load kg 90 / 100 Capacities			
Interior dimensions Number of seats Head area: 1st seat row / 2nd seat row / 3rd seat row mm 970 / 980 Head area: (glass sunroof): 1st seat row / 2nd seat row mm 952 / 980 row / 3rd seat row / 2nd seat row / 3rd seat row mm 952 / 980 row / 3rd seat row / 2nd seat row / 3rd seat row mm 1,053 / 960 Interior width: 1st seat row / 2nd seat row mm 1,466 / 1,511 / row Lugage compartment Length, rear seat raised/folded down mm 1,172 / 2,018 Width between wheel housings mm 1,000 Load height up to headlining mm 831 Volume by VDA measurement I 639 - 1,769 Lugage compartment opening: width/height mm 1,014 / 333 Weights Kerb weight (EU, incl. 75 kg driver) kg 1,670 - 1,851 Permitted gross weight kg 2,260 Payload from / to kg 484 - 665 Permitted axle load, front/rear kg 1,100 / 1,210 Allowable trailer weight up to 12% / 8% grade, braked kg 750 Permitted drawbar weight/roof load kg 90 / 100 Capacities	1		
Interior dimensions Number of seats Head area: 1st seat row / 2nd seat row / 3rd seat row mm 970 / 980 Head area (glass sunroof): 1st seat row / 2nd seat row mm 952 / 980 row / 3rd seat row Legroom: 1st seat row / 2nd seat row mm 1,053 / 960 Interior width: 1st seat row / 2nd seat row mm 1,466 / 1,511 / row Lugage compartment Length, rear seat raised/folded down mm 1,172 / 2,018 Width between wheel housings mm 1,000 Load height up to headlining mm 831 Volume by VDA measurement I 639 - 1,769 Luggage compartment opening: width/height mm 1,014 / 333 Weights Kerb weight (EU, incl. 75 kg driver) kg 1,670 - 1,851 Permitted gross weight kg 2,260 Payload from / to kg 484 - 665 Permitted axle load, front/rear kg 1,100 / 1,210 Allowable trailer weight, unbraked kg 750 Permitted drawbar weight/roof load Capacities	•		
Number of seats 5 Head area: 1st seat row / 2nd seat row / 3rd seat row mm 970 / 980 Head area (glass sunroof): 1st seat row / 2nd seat row mm 952 / 980 row / 3rd seat row mm 1,053 / 960 Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,466 / 1,511 / row Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,466 / 1,511 / row Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,466 / 1,511 / row Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,466 / 1,511 / row Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,466 / 1,511 / row Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,172 / 2,018 Width setter wish the seat row / 2nd seat row / 3rd seat row mm 1,172 / 2,018 Width between wheel housings mm 1,000 Length, rear seat raised/folded down mm 1,000 Width between wheel housings mm 1,000 Length, rear seat raised/folded down mm 1,000 <tr< td=""><td>·</td><td>111</td><td>11.4</td></tr<>	·	111	11.4
Head area: 1st seat row / 2nd seat row mm 970 / 980 Head area (glass sunroof): 1st seat row / 2nd seat mm 952 / 980 row / 3rd seat row Legroom: 1st seat row / 2nd seat row mm 1,053 / 960 Interior width: 1st seat row / 2nd seat row / 3rd seat row mm 1,466 / 1,511 / row Luggage compartment Length, rear seat raised/folded down mm 1,172 / 2,018 Width between wheel housings mm 1,000 Load height up to headlining mm 831 Volume by VDA measurement I 639 - 1,769 Luggage compartment opening: width/height mm 1,014 / 333 Weights Kerb weight (EU, incl. 75 kg driver) kg 1,670 - 1,851 Permitted gross weight kg 2,260 Payload from / to kg 1,100 / 1,210 Allowable trailer weight, unbraked kg 750 Permitted drawbar weight/roof load kg 90 / 100 Capacities			5
Head area (glass sunroof): 1st seat row / 2nd seat row / 3rd seat row 1,053 / 960 Interior width: 1st seat row / 2nd seat row / 3rd seat row 1,466 / 1,511 / row 1,172 / 2,018		mm	
row / 3rd seat row Legroom: 1st seat row / 2nd seat row / 3rd seat row Interior width: 1st seat row / 2nd seat row / 3rd seat row Luggage compartment Length, rear seat raised/folded down Midth between wheel housings Midth between wheel housings Mm Midth			
Legroom: 1st seat row / 2nd seat row / 3rd seat row mm 1,053 / 960 Interior width: 1st seat row / 2nd seat row / 3rd seat mm 1,466 / 1,511 / row Luggage compartment Length, rear seat raised/folded down mm 1,172 / 2,018 Width between wheel housings mm 1,000 Load height up to headlining mm 831 Volume by VDA measurement I 639 - 1,769 Luggage compartment opening: width/height mm 1,014 / 333 Weights Kerb weight (EU, incl. 75 kg driver) kg 1,670 - 1,851 Permitted gross weight kg 2,260 Payload from / to kg 484 - 665 Permitted axle load, front/rear kg 1,100 / 1,210 Allowable trailer weight up to 12% / 8% grade, braked kg 750 Permitted drawbar weight/roof load kg 90 / 100 Capacities		111111	552 / 560
Interior width: 1st seat row / 2nd seat row / 3rd seat row Luggage compartment Length, rear seat raised/folded down mm 1,172 / 2,018 Width between wheel housings mm 1,000 Load height up to headlining mm 831 Volume by VDA measurement I 639 - 1,769 Luggage compartment opening: width/height mm 1,014 / 333 Weights Kerb weight (EU, incl. 75 kg driver) kg 1,670 - 1,851 Permitted gross weight kg 2,260 Payload from / to kg 484 - 665 Permitted axle load, front/rear kg 1,100 / 1,210 Allowable trailer weight, unbraked kg 750 Permitted drawbar weight/roof load kg 90 / 100 Capacities		mm	1.053 / 960
rowLuggage compartmentLength, rear seat raised/folded downmm1,172 / 2,018Width between wheel housingsmm1,000Load height up to headliningmm831Volume by VDA measurementI639 - 1,769Luggage compartment opening: width/heightmm1,014 / 333WeightsKerb weight (EU, incl. 75 kg driver)kg1,670 - 1,851Permitted gross weightkg2,260Payload from / tokg484 - 665Permitted axle load, front/rearkg1,100 / 1,210Allowable trailer weight up to 12% / 8% grade, brakedkg2,200 / 2,200Allowable trailer weight, unbrakedkg750Permitted drawbar weight/roof loadkg90 / 100Capacities			
Length, rear seat raised/folded down mm 1,172 / 2,018 Width between wheel housings mm 1,000 Load height up to headlining mm 831 Volume by VDA measurement I 639 - 1,769 Luggage compartment opening: width/height mm 1,014 / 333 Weights Kerb weight (EU, incl. 75 kg driver) kg 1,670 - 1,851 Permitted gross weight kg 2,260 Payload from / to kg 484 - 665 Permitted axle load, front/rear kg 1,100 / 1,210 Allowable trailer weight up to 12% / 8% grade, braked kg 750 Permitted drawbar weight/roof load kg 90 / 100 Capacities			, , , , , ,
Length, rear seat raised/folded down mm 1,172 / 2,018 Width between wheel housings mm 1,000 Load height up to headlining mm 831 Volume by VDA measurement I 639 - 1,769 Luggage compartment opening: width/height mm 1,014 / 333 Weights Kerb weight (EU, incl. 75 kg driver) kg 1,670 - 1,851 Permitted gross weight kg 2,260 Payload from / to kg 484 - 665 Permitted axle load, front/rear kg 1,100 / 1,210 Allowable trailer weight up to 12% / 8% grade, braked kg 750 Permitted drawbar weight/roof load kg 90 / 100 Capacities	Luggage compartment		
Width between wheel housings mm 1,000 Load height up to headlining mm 831 Volume by VDA measurement I 639 - 1,769 Luggage compartment opening: width/height mm 1,014 / 333 Weights Kerb weight (EU, incl. 75 kg driver) kg 1,670 - 1,851 Permitted gross weight kg 2,260 Payload from / to kg 484 - 665 Permitted axle load, front/rear kg 1,100 / 1,210 Allowable trailer weight up to 12% / 8% grade, braked kg 750 Permitted drawbar weight/roof load kg 90 / 100 Capacities	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	mm	1,172 / 2,018
Volume by VDA measurement Luggage compartment opening: width/height Weights Kerb weight (EU, incl. 75 kg driver) Permitted gross weight Payload from / to Payload from / to Permitted axle load, front/rear Allowable trailer weight up to 12% / 8% grade, braked Allowable trailer weight, unbraked Permitted drawbar weight/roof load Capacities			
Volume by VDA measurement Luggage compartment opening: width/height Weights Kerb weight (EU, incl. 75 kg driver) Permitted gross weight Payload from / to Payload from / to Permitted axle load, front/rear Allowable trailer weight up to 12% / 8% grade, braked Allowable trailer weight, unbraked Permitted drawbar weight/roof load Capacities	•		831
Weights Kerb weight (EU, incl. 75 kg driver) kg 1,670 - 1,851 Permitted gross weight kg 2,260 Payload from / to kg 484 - 665 Permitted axle load, front/rear kg 1,100 / 1,210 Allowable trailer weight up to 12% / 8% grade, braked kg 2,200 / 2,200 Allowable trailer weight, unbraked kg 750 Permitted drawbar weight/roof load kg 90 / 100 Capacities	Volume by VDA measurement	1	
Kerb weight (EU, incl. 75 kg driver) kg 1,670 - 1,851 Permitted gross weight kg 2,260 Payload from / to kg 484 - 665 Permitted axle load, front/rear kg 1,100 / 1,210 Allowable trailer weight up to 12% / 8% grade, braked kg 2,200 / 2,200 Allowable trailer weight, unbraked kg 750 Permitted drawbar weight/roof load kg 90 / 100 Capacities	Luggage compartment opening: width/height	mm	1,014 / 333
Permitted gross weight kg 2,260 Payload from / to kg 484 - 665 Permitted axle load, front/rear kg 1,100 / 1,210 Allowable trailer weight up to 12% / 8% grade, braked kg 2,200 / 2,200 Allowable trailer weight, unbraked kg 750 Permitted drawbar weight/roof load kg 90 / 100 Capacities	Weights		
Payload from / to kg 484 - 665 Permitted axle load, front/rear kg 1,100 / 1,210 Allowable trailer weight up to 12% / 8% grade, braked kg 2,200 / 2,200 Allowable trailer weight, unbraked kg 750 Permitted drawbar weight/roof load kg 90 / 100 Capacities		kg	1,670 - 1,851
Payload from / to kg 484 - 665 Permitted axle load, front/rear kg 1,100 / 1,210 Allowable trailer weight up to 12% / 8% grade, braked kg 2,200 / 2,200 Allowable trailer weight, unbraked kg 750 Permitted drawbar weight/roof load kg 90 / 100 Capacities	Permitted gross weight	_	2,260
Allowable trailer weight up to 12% / 8% grade, braked kg 2,200 / 2,200 Allowable trailer weight, unbraked kg 750 Permitted drawbar weight/roof load kg 90 / 100 Capacities	, ·		484 - 665
Allowable trailer weight, unbraked kg 750 Permitted drawbar weight/roof load kg 90 / 100 Capacities		kg	1,100 / 1,210
Permitted drawbar weight/roof load kg 90 / 100 Capacities			
Capacities		kg	
·	Permitted drawbar weight/roof load	kg	90 / 100
Fuel tank I 66	•		
	Fuel tank	<u> </u>	66

Passat Alltrack 2.0 TDI BMT		140 kW (190 PS)
Engine, electrics		
Type of engine	-	4-cyl. diesel engine TDI BMT
Effective displacement	cm ³	1,968
Valves per cylinder Injection / Charge		4 Common Rail / Turbocharger
Power output		140 (190) kW (PS) 3,500 - 4,000 at rpm
Max. torque	Nm at rpm	400 / 1,900 - 3,300
Alternator	A	140
Driving performance data		
Acceleration 0 - 80/100 km/h	S	5.5 / 8
Top speed	km/h	220
Fuel consumption		5
Fuel type	1/4.001	Diesel min. 51 CN
Urban	l/100km	6.1 - 6
Extra-urban	l/100km l/100km	4.7 - 4.6
Combined cycle		5.2 - 5.1 137 - 135
CO2 emissions, combined NOx	g/km mg/km	36.2
Particulates	mg/km	0.21
Efficiency label	mg/Km	B - A
Exhaust emissions classification		Euro 6
Power transmission		
Gearbox		Six-speed direct shift gearbox
		(DSG) 4MOTION four-wheel drive
Exterior dimensions		
Number of doors		4
Length	mm	4,777 - 4,882
Width	mm	1,832 - 1,832
Height	mm	1,506 - 1,530
Length with towing bracket (maximum length)	mm	4,882
Width with door mirrors Wheelbase	mm	2,062 2,789
Track, front / rear	mm mm	1,582 / 1,565
Approach angle / departure angle	0	13.4 / 12.3
Breakover angle	0	10.5
Turning circle	m	11.4
Interior dimensions		
Number of seats		5
Head area: 1st seat row / 2nd seat row / 3rd seat row	mm	970 / 980
Head area (glass sunroof): 1st seat row / 2nd seat	mm	952 / 980
row / 3rd seat row		4.050 / 000
Legroom: 1st seat row / 2nd seat row / 3rd seat row	mm	1,053 / 960 1,466 / 1,511 /
Interior width: 1st seat row / 2nd seat row / 3rd seat row	mm	1,466 / 1,511 /
Luggage compartment		
Length, rear seat raised/folded down	mm	1,172 / 2,018
Width between wheel housings	mm	1,000
Load height up to headlining	mm	831
Volume by VDA measurement	1	639 - 1,769
Luggage compartment opening: width/height	mm	1,014 / 333
Weights		
Kerb weight (EU, incl. 75 kg driver)	kg	1,705 - 1,887
Permitted gross weight	kg	2,290
Payload from / to	kg	478 - 660
Permitted axle load, front/rear	kg	1,120 / 1,220
Allowable trailer weight up to 12% / 8% grade, braked	kg	2,200 / 2,200
Allowable trailer weight, unbraked	kg	750 00 / 100
Permitted drawbar weight/roof load	kg	90 / 100
Capacities Fuel tank	1	66
i uei talik	<u>I</u>	00

Passat Alltrack 2.0 TDI SCR BMT		176 kW (239 PS)
Engine, electrics		
Type of engine		4-cyl diesel engine TDI SCR BMT
Effective displacement	cm³	1,968
Valves per cylinder		4
Injection / Charge		Common Rail / Turbocharger
Power output	Nm at ram	176 (239) kW (PS) - 4,000 at rpm
Max. torque Alternator	Nm at rpm A	500 / 1,750 - 2,500 140
Driving performance data		1.10
Acceleration 0 - 80/100 km/h	s	4.3 / 6.4
Top speed	km/h	234
Fuel consumption		· · · · · · · · · · · · · · · · · · ·
Fuel type		Diesel min. 51 CN
Urban	l/100km	6.6
Extra-urban	l/100km	4.9 - 4.8
Combined cycle	l/100km	5.5
CO2 emissions, combined	g/km	145 - 144
NOx	mg/km	49.8
Particulates	mg/km	0
Efficiency label		B Furo 6
Exhaust emissions classification		Euro 6
Power transmission Gearbox		Savon apped direct shift assurbay
Gearbox		Seven-speed direct shift gearbox (DSG), 4MOTION four-wheel drive
Exterior dimensions		
Number of doors		4
Length	mm	4,777 - 4,882
Width	mm	1,832 - 1,832
Height	mm	1,506 - 1,530
Length with towing bracket (maximum length) Width with door mirrors	mm	4,882 2,062
Wheelbase	mm mm	2,062
Track, front / rear	mm	1,582 / 1,565
Approach angle / departure angle	0	13.4 / 12.3
Breakover angle	o	10.5
Turning circle	m	11.4
Interior dimensions		
Number of seats		5
Head area: 1st seat row / 2nd seat row / 3rd seat row	mm	970 / 980
Head area (glass sunroof): 1st seat row / 2nd seat	mm	952 / 980
row / 3rd seat row		4.050./.000
Legroom: 1st seat row / 2nd seat row / 3rd seat row	mm	1,053 / 960
Interior width: 1st seat row / 2nd seat row / 3rd seat row	mm	1,466 / 1,511 /
Luggage compartment Length, rear seat raised/folded down	mm	1,172 / 2,018
Width between wheel housings	mm	1,17272,018
Load height up to headlining	mm	831
Volume by VDA measurement	1	639 - 1,769
Luggage compartment opening: width/height	mm	1,014 / 333
Weights		
Kerb weight (EU, incl. 75 kg driver)	kg	1,776 - 1,965
Permitted gross weight	kg	2,360
Payload from / to	kg	470 - 659
Permitted axle load, front/rear	kg	1,160 / 1,250
Allowable trailer weight up to 12% / 8% grade, braked	kg	2,200 / 2,200
Allowable trailer weight, unbraked	kg	750
Permitted drawbar weight/roof load	kg	90 / 100
Capacities		
Fuel tank	<u> </u>	66

Passat Alltrack 2.0 TSI BMT		162 kW (220 PS)
Engine, electrics		
Type of engine		4-cyl. petrol engine TSI BMT
Effective displacement	cm ³	1,984
Valves per cylinder		4
Injection / Charge		Direct injection / Turbocharger
Power output	Nm at ram	162 (220) kW (PS) 4,420 - 6,250 at rpm
Max. torque Alternator	Nm at rpm A	350 / 1,500 - 4,400 140
Driving performance data	A	140
Acceleration 0 - 80/100 km/h	s	4.7 / 6.8
Top speed	km/h	231
Fuel consumption	,	
Fuel type		Premium min. 95 RON
Urban	l/100km	8.5
Extra-urban	l/100km	6
Combined cycle	l/100km	6.9
CO2 emissions, combined	g/km	158 - 157
NOx	mg/km	42.1
Particulates	mg/km	0.15
Efficiency label		C
Exhaust emissions classification		Euro 6
Power transmission		Occupance of Paris 177
Gearbox		Seven-speed direct shift gearbox (DSG), 4MOTION four-wheel drive
Exterior dimensions		
Number of doors		4
Length	mm	4,777 - 4,882
Width	mm	1,832 - 1,832
Height Length with towing bracket (maximum length)	mm mm	1,506 - 1,530 4,882
Width with door mirrors	mm	2,062
Wheelbase	mm	2,789
Track, front / rear	mm	1,582 / 1,565
Approach angle / departure angle	0	13.4 / 12.3
Breakover angle	0	10.5
Turning circle	m	11.4
Interior dimensions		
Number of seats		5
Head area: 1st seat row / 2nd seat row / 3rd seat row	mm	970 / 980
Head area (glass sunroof): 1st seat row / 2nd seat	mm	952 / 980
row / 3rd seat row Legroom: 1st seat row / 2nd seat row / 3rd seat row	mm	1,053 / 960
Interior width: 1st seat row / 2nd seat row / 3rd seat row / 3rd seat row / 2nd seat row / 3rd s	mm mm	1,466 / 1,511 /
row	******	1,100,1,011,
Luggage compartment		
Length, rear seat raised/folded down	mm	1,172 / 2,018
Width between wheel housings	mm	1,000
Load height up to headlining	mm	831
Volume by VDA measurement	1	639 - 1,769
Luggage compartment opening: width/height	mm	1,014 / 333
Weights		
Kerb weight (EU, incl. 75 kg driver)	kg	1,677 - 1,866
Permitted gross weight	kg	2,270
Payload from / to	kg	479 - 668
Permitted axle load, front/rear	kg	1,080 / 1,240
Allowable trailer weight up to 12% / 8% grade, braked	kg	2,200 / 2,200
Allowable trailer weight, unbraked	kg	750 00 / 100
Permitted drawbar weight/roof load	kg	90 / 100
Capacities		00
Fuel tank	l	66

